




PERMALOC CORPORATION
 13505 BARRY ST
 HOLLAND, MI 49424
 TOLL FREE: 1-800-356-9660
 PHONE: (616) 399-9600
 FAX: (616) 399-9770
 www.permaloc.com

SELECT DESIRED SIZE:


- 1/8" X 3 1/2" (3.2 MM X 89 MM), 0.06" (1.52 MM) THICK WITH 0.2" (5.08 MM) EXPOSED TOP LIP
- 3/16" X 3 1/2" (4.8 MM X 89 MM), 0.076" (1.93 MM) THICK WITH 0.2" (4.83 MM) EXPOSED TOP LIP
- 1/8" X 4" (3.2 MM X 101.6 MM), 0.06" (1.52 MM) THICK WITH 0.2" (5.08 MM) EXPOSED TOP LIP
- 3/16" X 4" (4.8 MM X 101.6 MM), 0.076" (1.93 MM) THICK WITH 0.2" (4.83 MM) EXPOSED TOP LIP
- 1/8" X 6" (3.2 MM X 152.4 MM), 0.06" (1.52 MM) THICK WITH 0.2" (5.08 MM) EXPOSED TOP LIP
- 3/16" X 6" (4.8 MM X 152.4 MM), 0.076" (1.93 MM) THICK WITH 0.2" (4.83 MM) EXPOSED TOP LIP

SELECT DESIRED FINISH:

- MF - MILL FINISH-NATURAL ALUMINUM
- BL - BLACK DURAFLEX-ELECTROSTATICALLY APPLIED BAKED ON PAINT, MEETS AAMA 2603



ISOMETRIC VIEW




SIDE VIEW

NOTES:

1. 8'-0" (2.44 M) SECTIONS TO INCLUDE (3) 12" (305 MM) ALUMINUM STAKES.
2. 16'-0" (4.88 M) SECTIONS TO INCLUDE (8) 12" (305 MM) ALUMINUM STAKES.
3. CORNERS: NOTCH BASE ONLY AND FORM A CONTINUOUS CORNER.
4. PERMALOC PERMASTRIP AS MANUFACTURED BY PERMALOC CORPORATION.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 006-046



PERMASTRIP™ ALUMINUM MAINTENANCE STRIP

AGGREGATE WALKWAY - STONE AND TURF CAD FILES PS-2